

TOP HAT HOT SHOT FLOAT TRAILERS

OTW HSF MODEL • 25900 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
40x102" OTW HSF 25.9K	2-12000#	ST235/16 LRE	12000#	25900#
42x102" OTW HSF 25.9K	Oil Bath			
44x102" OTW HSF 25.9K				
46x102" OTW HSF 25.9K				
48x102" OTW HSF 25.9K				

STANDARD EQUIPMENT:

Coupler: King Pin
 Jack: Dual 2-Speed
 Floor: 2" Treated Pine
 Brake: Electric All Wheel w/BAU
 Stake Pockets & Rubrail
 Spare Tire & Rack
 DOT Reflective Tape
 Driver & Curb Side Steps w/Grab Handles
 Low Profile
 Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x19# I-Beam
 Crossmembers: 3" Channel, 16" OC
 Side Rails: 8" Channel w/ 3/8x2 Rubrail
 Frame to Crossmember Gussets
 Bridge Support Truss
 Anti Flex Torque

Trailers may be shown with optional equipment. Additional Options may be available.



Top Hat TRAILERS

O.T.W. Gooseneck Series



Top Hat
 industries, inc.

MANUFACTURER OF
 UTILITY, EQUIPMENT, CATTLE, AND CARGO TRAILERS

P.O. Box 40
 Naples, TX 75568

"Quality Trailers Since 1983"

DEALER INFORMATION



To find a dealer near you visit us on the web at:
www.tophattrailers.com

**IF IT HAS THE Top Hat BRAND,
 YOU KNOW IT'S TOP QUALITY.**

TOP HAT OTW GOOSENECK TRAILERS

OTW GN MODEL • 14000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20x102" OTW GN 14K	2-7000#	ST235/16 LRE	6840#	14000#
22x102" OTW GN 14K	Ultra Lube			
24x102" OTW GN 14K				
26x102" OTW GN 14K				
28x102" OTW GN 14K				
30x102" OTW GN 14K				
32x102" OTW GN 14K				

OTW GN MODEL • 18000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
28x102" OTW GN 18K	3-7000#	ST235/16 LRE	6840#	18000#
30x102" OTW GN 18K	Ultra Lube			
32x102" OTW GN 18K				
34x102" OTW GN 18K				
36x102" OTW GN 18K				

STANDARD EQUIPMENT:

Coupler: 2 5/16" Round Adjustable	Chain Tray
Jack: Dual 10000# Drop Leg	DOT Reflective Tape
Floor: 2" Treated Pine	Driver & Curb Side Steps w/Grab Handles
Brake: Electric All Wheel w/BAU	Spring Ride axles
Stake Pockets & Rubrail	Square Back w/Ramp Bar
Spare Tire & Rack	Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x14# I-Beam on 14K. 16# on 18K
 Neck: 14K is 8" Channel. 18K is 12"x16# I-Beam
 Crossmembers: 3" Channel. 24" OC
 Side Rails: 5x3x1/4 w/ 3/8x2 Rubrail
 Frame to Crossmember Strutts
 Bridge Support Truss
 Anti Flex Torque on 32' or longer
 Deck Height 36"



Trailers may be shown with optional equipment.

Additional Options may be available.

TOP HAT OTW GOOSENECK DOVETAIL TRAILERS

OTW GN DT MODEL • 14000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20+5x102" OTW GN DT 14K	2-7000#	ST235/16 LRE	6840#	14000#
21+5x102" OTW GN DT 14K	Ultra Lube			
22+5x102" OTW GN DT 14K				
23+5x102" OTW GN DT 14K				
24+5x102" OTW GN DT 14K				

OTW GN DT MODEL • 18000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
25+5x102" OTW GN DT 18K	3-7000#	ST235/16 LRE	6840#	18000#
26+5x102" OTW GN DT 18K	Ultra Lube			
27+5x102" OTW GN DT 18K				
28+5x102" OTW GN DT 18K				
29+5x102" OTW GN DT 18K				
30+5x102" OTW GN DT 18K				

STANDARD EQUIPMENT:

Coupler: 2 5/16" Round Adjustable	Chain Tray
Jack: Dual 10000# Drop Leg	DOT Reflective Tape
Floor: 2" Treated Pine	Driver & Curb Side Steps w/Grab Handles
Brake: Electric All Wheel w/BAU	Spring Ride Axles
Stake Pockets & Rubrail	Dovetail w/Fold Over Spring Assist Ramps
Spare Tire & Rack	Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x14# I-Beam on 14K. 16# on 18K
 Neck: 14K is 8" Channel. 18K is 12"x16# I-Beam
 Crossmembers: 3" Channel. 24" OC
 Side Rails: 5x3x1/4 w/3/8x2 Rubrail
 Frame to Crossmember Strutts
 Bridge Support Truss
 Anti Flex Torque on 32' or longer
 Deck Height 36"



Trailers may be shown with optional equipment.

Additional Options may be available.

TOP HAT OTW GOOSENECK TRAILERS

OTW GN MODEL • 25900 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20x102" OTW GN 25.9K	2-12000#	ST235/16 LRE	12000#	25900#
22x102" OTW GN 25.9K	Oil Bath			
24x102" OTW GN 25.9K				
26x102" OTW GN 25.9K				
28x102" OTW GN 25.9K				
30x102" OTW GN 25.9K				
32x102" OTW GN 25.9K				
34x102" OTW GN 25.9K				
36x102" OTW GN 25.9K				
38x102" OTW GN 25.9K				
40x102" OTW GN 25.9K				

OTW GN DT MODEL • 25900 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20+5x102" OTW GN DT 25.9K	2-12000#	ST235/16 LRE	12000#	25900#
21+5x102" OTW GN DT 25.9K	Oil Bath			
22+5x102" OTW GN DT 25.9K				
23+5x102" OTW GN DT 25.9K				
24+5x102" OTW GN DT 25.9K				
25+5x102" OTW GN DT 25.9K				
26+5x102" OTW GN DT 25.9K				
27+5x102" OTW GN DT 25.9K				
28+5x102" OTW GN DT 25.9K				
29+5x102" OTW GN DT 25.9K				
30+5x102" OTW GN DT 25.9K				
31+5x102" OTW GN DT 25.9K				
32+5x102" OTW GN DT 25.9K				
33+5x102" OTW GN DT 25.9K				
34+5x102" OTW GN DT 25.9K				
35+5x102" OTW GN DT 25.9K				

STANDARD EQUIPMENT:

Coupler: 2 5/16" Square Load Leveler
Jack: Dual 2-Speed
Floor: 2" Treated Pine
Brake: Electric All Wheel w/BAU
Stake Pockets & Rubrail
Spare Tire & Rack
Lockable Toolbox Between Risers
DOT Reflective Tape
D-Rings
Driver & Curb Side Steps w/Grab Handles
Dovetail w/Fold Over Spring Assist Ramps on DT Model
Square Back w/Ramp Bar on Non DT Model
Low Profile
Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x19# I-Beam
 Neck: Same as Frame
 Crossmembers: 3" Channel 16" OC Thru Frame w/
 Each 4th Crossmember 4" Channel
 Side Rails: 8" Channel w/ 3/8x2 Rubrail
 Frame to Crossmember Gussets
 Bridge Support Truss
 Anti Flex Torque
 Deck Height: 34.5"



Trailers may be shown with optional equipment.

Additional Options may be available.

TOP HAT OTW GOOSENECK TRAILERS

OTW GN MODEL • 20000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20x102" OTW GN 20K	2-10000#	7:50/16 LRE	9880#	20000#
22x102" OTW GN 20K	Oil Bath			
24x102" OTW GN 20K				
26x102" OTW GN 20K				
28x102" OTW GN 20K				

OTW GN DT MODEL • 20000 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20+5x102" OTW GN DT 20K	2-10000#	7:50/16 LRE	9880#	20000#
21+5x102" OTW GN DT 20K	Oil Bath			
22+5x102" OTW GN DT 20K				
23+5x102" OTW GN DT 20K				
24+5x102" OTW GN DT 20K				

STANDARD EQUIPMENT:

Coupler: 2 5/16" Round Adjustable
 Jack: Dual 10000# Drop Leg
 Floor: 2" Treated Pine
 Brake: Electric All Wheel w/BAU
 Stake Pockets & Rubrail
 Spare Tire & Rack
 Chain Tray
 DOT Reflective Tape
 Driver & Curb Side Steps w/Grab Handles
 Dovetail w/Fold Over Spring Assist Ramps on DT Model
 Square Back w/Ramp Bar on Non DT Model
 Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x14# I-Beam
 Neck: 12"x14# I-Beam
 Crossmembers: 3" Channel, 24" OC
 Side Rails: 5x3x1/4 w/ 3/8x2 Rubrail
 Frame to Crossmember Struts
 Bridge Support Truss
 Anti Flex Torque on 32' or longer
 Deck Height 36"



Trailers may be shown with optional equipment.

Additional Options may be available.

TOP HAT OTW GOOSENECK TRAILERS

OTW GN MODEL • 22500 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20x102" OTW GN 22.5K	2-10000#	ST235/16 LRE	10000#	22500#
22x102" OTW GN 22.5K	Oil Bath			
24x102" OTW GN 22.5K				
26x102" OTW GN 22.5K				
28x102" OTW GN 22.5K				
30x102" OTW GN 22.5K				
32x102" OTW GN 22.5K				
34x102" OTW GN 22.5K				
36x102" OTW GN 22.5K				
38x102" OTW GN 22.5K				
40x102" OTW GN 22.5K				



OTW GN DT MODEL • 22500 SERIES

MODEL	AXLE	TIRES	GAWR	GVWR
20+5x102" OTW GN DT 22.5K	2-10000#	ST235/16 LRE	10000#	22500#
21+5x102" OTW GN DT 22.5K	Oil Bath			
22+5x102" OTW GN DT 22.5K				
23+5x102" OTW GN DT 22.5K				
24+5x102" OTW GN DT 22.5K				
25+5x102" OTW GN DT 22.5K				
26+5x102" OTW GN DT 22.5K				
27+5x102" OTW GN DT 22.5K				
28+5x102" OTW GN DT 22.5K				
29+5x102" OTW GN DT 22.5K				
30+5x102" OTW GN DT 22.5K				
31+5x102" OTW GN DT 22.5K				
32+5x102" OTW GN DT 22.5K				
33+5x102" OTW GN DT 22.5K				
34+5x102" OTW GN DT 22.5K				
35+5x102" OTW GN DT 22.5K				



STANDARD EQUIPMENT:

Coupler: 2 5/16" Square Load Leveler
 Jack: Dual 10000# Drop Leg
 Floor: 2" Treated Pine
 Brake: Electric All Wheel w/BAU
 Stake Pockets & Rubrail
 Spare Tire & Rack
 Lockable Toolbox Between Risers
 DOT Reflective Tape
 Driver & Curb Side Steps w/Grab Handles
 Dovetail w/Fold Over Spring Assist Ramps on DT Model
 Square Back w/Ramp Bar on Non DT Model
 Color: Standard Color

FRAME STRUCTURE:

Frame: 12"x16# I-Beam thru 32'; 19# over 32'
 Neck: Same as Frame
 Crossmembers: 3" Channel, 16" OC
 Side Rails: 6" Channel w/ 3/8x2 Rubrail
 Frame to Crossmember Gussets
 Bridge Support Truss
 Anti Flex Torque on 32' or longer
 Deck Height: 36"

Trailers may be shown with optional equipment.

Additional Options may be available.